RECEIVED CENTRAL FAX CENTER APR 0 3 2009

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended) An article with an organic-inorganic composite film, the article comprising a substrate and an organic-inorganic composite film that is formed on a surface of the substrate and contains an organic material and an inorganic oxide,

wherein the organic inorganic composite film contains a hydrophilic organic polymer as the organic material,

the organic-inorganic composite film contains a network structure of silica in a form of siloxane polymer as the inorganic oxide,

the organic-inorganic composite film contains the silica as its main component, and

the organic-inorganic composite film contains a hydrophilic organic polymer as the organic material in the network structure of silica, and

the organic-inorganic composite film does not separate from the substrate after the Taber abrasion test prescribed in Japanese Industrial Standards R 3212 that is carried out with respect to a surface of the organic-inorganic composite film, the Taber abrasion test being carried out at a rotation number of 1000 with a load of 500 g being applied.

- 2. (Original) The article according to claim 1, wherein the organic-inorganic composite film has a thickness of more than 250 nm but not more than 5 μ m.
- 3. (Original) The article according to claim 2, wherein the organic-inorganic composite film has a thickness of more than 300 nm but not more than 5 μ m.
- 4. (Original) The article according to claim 3, wherein the organic-inorganic composite film has a thickness of 1 μ m to 5 μ m.

- 5. (Original) The article according to claim 1, wherein a portion that has been subjected to the Taber abrasion test has a haze ratio of 4% or lower after the Taber abrasion test.
- 6. (Cancelled)
- 7. (Original) The article according to claim 1, wherein the organic-inorganic composite film contains phosphorus.
- 8. (Cancelled)
- 9. (Previously presented) The article according to claim 1, wherein the hydrophilic organic polymer includes a polyoxyalkylene group.
- 10. (Original) The article according to claim 1, wherein the organic-inorganic composite film contains fine particles.
- 11. (Original) The article according to claim 10, wherein the content of the fine particles is at least 1 mass%, and a portion that has been subjected to the Taber abrasion test has a haze ratio of 4% or lower after the Taber abrasion test.
- 12 21. (Cancelled)
- 22. (Previously presented) The article according to claim 1, wherein the substrate is a glass sheet.
- 23 24. (Cancelled)
- 25. (Withdrawn currently amended) An article with an organic-inorganic composite film, the article comprising a substrate and an organic-inorganic composite

film that is formed on a surface of the substrate and contains an organic material and an inorganic oxide,

wherein the organic-inorganic composite film contains a network structure of silica in a form of siloxane polymer as the inorganic oxide,

the organic-inorganic composite film contains the silica as its main component, the organic-inorganic composite film contains no fine particles,

the substrate is a glass sheet,

the organic-inorganic composite film contains the organic material in the network structure of silica, and

the organic-inorganic composite film does not separate from the substrate after the Taber abrasion test prescribed in Japanese Industrial Standards R 3212 that is carried out with respect to a surface of the organic-inorganic composite film, the Taber abrasion test being carried out at a rotation number of 1000 with a load of 500 g being applied.

26. (Cancelled)

27. (Currently Amended) An article with an organic-inorganic composite film, the article comprising a substrate and an organic-inorganic composite film that is formed on a surface of the substrate and contains an organic material and an inorganic oxide,

wherein the organic-inorganic composite film contains a network structure of silica in a form of siloxane polymer as the inorganic oxide,

the organic-inorganic composite film contains the silica as its main component, the organic-inorganic composite film contains fine particles of electrically conductive oxide,

the organic-inorganic composite film contains the organic material in the network structure of silica, and

the organic-inorganic composite film does not separate from the substrate after the Taber abrasion test prescribed in Japanese Industrial Standards R 3212 that is carried out with respect to a surface of the organic-inorganic composite film, the Taber abrasion test being carried out at a rotation number of 1000 with a load of 500 g being applied.

28. (Cancelled)